

# Wall Primer

Interior



Nature Coat **Interior Wall Primer** is a pure water based Acrylic, Water thinnable eco-friendly product with no added lead/mercury, specially formulated to suit your Interior Walls. This special formulation ensures extra-ordinary performance and a 10 year protection against fungus/ algae growth, flaking and chalking.

**Premium Features:**

- High resistance to weathering
- Superior resistance to fungus/ algae growth, flaking and chalking
- Peel resistance
- Fade resistance
- UV resistance
- 10 year protection
- Efflorescence resistant

**Factory Address:** SM3 Quality Chemicals, Factory Hall-17, SDF building, KSIDC Investment Zone, Canalpirivu, Pampampallam (P.O), Pudhussery East, Palakkad - 678621

**Phone:** +91 9745 285 555, +91 8606 060 300

**Email:** [marketing@naturecoatpaints.com](mailto:marketing@naturecoatpaints.com) | **Website:** [www.naturecoatpaints.com](http://www.naturecoatpaints.com)

# Wall Primer Interior

No.	PARAMETERS	VALUES
1.	Physical Appearance	Translucent Off White
2.	Coating Type	Acrylic Water Base
3.	Volatile Organic Compound	Low VOC
4.	Toxicity	Non-Toxic
5.	Water Absorption	Low
6.	Fungus Resistance	No
7.	Damp Resistance	High
8.	Coverage	130 Sqft/kg
9.	Mixing Ratio	4:1 (By Volume)
10.	Product Base	Water
11.	Thinning Liquid	Water
12.	Density	1.3
13.	Touch Dry Time	10 mins
14.	Re-Coating Time	30 mins
15.	Curing Time	4 hrs
16.	Dry Film Thickness	40 microns
17.	Curing Mechanism	Atmospheric
18.	Application Method	Brush / Spray / Roller
19.	Comply to	IS 15489

**Factory Address:** SM3 Quality Chemicals, Factory Hall-17, SDF building, KSIDC Investment Zone, Canalpirivu, Pampampallam (P.O), Pudhussery East, Palakkad - 678621

**Phone:** +91 9745 285 555, +91 8606 060 300

**Email:** marketing@naturecoatpaints.com | **Website:** www.naturecoatpaints.com