

# Wall Primer

## Exterior



Nature Coat **Exterior Wall Primer** is a pure water based Acrylic, Water thinnable eco-friendly product with no added lead/mercury, specially formulated to suit your Exterior Walls. This special formulation ensures extra-ordinary performance and a 10 year protection against fungus/ algae growth, flaking and chalking.

### **Premium Features:**

- High resistance to weathering
- Superior resistance to fungus/ algae growth, flaking and chalking
- Peel resistance
- Fade resistance
- UV resistance
- 10 year protection
- Efflorescence resistant

**Factory Address:** SM3 Quality Chemicals, Factory Hall-17, SDF building, KSIDC Investment Zone, Canalpirivu, Pampampallam (P.O), Pudhussery East, Palakkad - 678621

**Phone:** +91 9745 285 555, +91 8606 060 300

**Email:** [marketing@naturecoatpaints.com](mailto:marketing@naturecoatpaints.com) | **Website:** [www.naturecoatpaints.com](http://www.naturecoatpaints.com)

# Wall Primer Exterior

| No. | PARAMETERS                | VALUES             |
|-----|---------------------------|--------------------|
| 1.  | Physical Appearance       | Milky White        |
| 2.  | Coating Type              | Acrylic Water Base |
| 3.  | Volatile Organic Compound | Low VOC            |
| 4.  | Toxicity                  | Non-Toxic          |
| 5.  | Water Absorption          | Low                |
| 6.  | Fungus Resistance         | No                 |
| 7.  | Damp Resistance           | High               |
| 8.  | Coverage                  | 150 Sqft/kg        |
| 9.  | Mixing Ratio              | 4:1 (By Volume)    |
| 10. | Product Base              | Water              |
| 11. | Thinning Liquid           | Water              |
| 12. | Density                   | 1.3                |
| 13. | Touch Dry Time            | 15 mins            |
| 14. | Re-Coating Time           | 40 mins            |
| 15. | Curing Time               | 4 hrs              |
| 16. | Dry Film Thickness        | 90 microns         |
| 17. | Curing Mechanism          | Atmospheric        |
| 18. | Comply to                 | IS 15489           |

**Factory Address:** SM3 Quality Chemicals, Factory Hall-17, SDF building, KSIDC Investment Zone, Canalpirivu, Pampampallam (P.O), Pudhussery East, Palakkad - 678621

**Phone:** +91 9745 285 555, +91 8606 060 300

**Email:** marketing@naturecoatpaints.com | **Website:** www.naturecoatpaints.com